# **SB006** 150X150X100 **Grade A** BS 5834-2

# **Multi**Grip<sup>™</sup> Ductile Iron Surface Box ecclesutilities®





Capable of being used in carriageways and other areas carring fast moving, normal commercial vehicles with wheel loads up to 5 tonnes and slow moving, specially authorised vehicles with wheel up to 11.5 tonnes.

## **OPTIONAL EXTRAS:**

**Badged** 



| <b>Product Code</b> | Clear Opening | Base Size     | Depth |
|---------------------|---------------|---------------|-------|
| SB006               | 150mm x 150mm | 232mm x 232mm | 100mm |

### **FEATURES:**



SmartGrip Technology™ - Unique pattern design provides a PSRV value of >70



Ratio - Ductile iron for improved weight



Strong & Durable - Spheroidal graphite cast



Wedged Seated - The cover features our



Recyclable - Long life asset with high



Mortar Level Indicator - Shows when the



QR Code Mobile Friendly - Clear, easy-to -use GR Code to access installation instructions



**Indicator Coating Layer - Black coated** 



Open Keyway - Facilities easy access to the



Indexed Lid - Provides one way fitting.



# **SB006** 150X150X100 **Grade A** BS 5834-2

# **Multi**Grip<sup>™</sup> Ductile Iron Surface Box ecclesutilities®





Capable of being used in carriageways and other areas carring fast moving, normal commercial vehicles with wheel loads up to 5 tonnes and slow moving, specially authorised vehicles with wheel up to 11.5 tonnes.

### **DATA**

#### **Dimensions**

A/ Base Size: 232mm x 232mm B/ Clear Opening: 150mmx150mm C/ Depth: 100mm

#### Materials

Ductile Iron

#### Finish

**Black Coated** 

#### Standard

BS 5834-2

#### **Product Type**


**Ductile Iron Surface Box** 


Additional Feature

**Smart Coat** 


## **Smart**Grip Technology

Disclaimer: Eccles (UK Foundries FE) Ltd are continually seeking to improve our products and we therefore reserve the right to alter product specifications without reserve the right to after product specifications without prior notice. It is the responsibility of all users to ensure that the above product data is current. Installation details are available on request. It is always recommended that the use of road plates be used where access covers, guilty grates and frames are exposed to construction and site traffic during the construction place of severe and in accordance. construction phase of any project and in accordance with "Annex F" EN124\_1:2015





8






DIAGRAM KEY: A

**BASE SIZE** 

B CLEAR OPENING

C FRAME DEPTH

